

The logo for AUMOS, featuring the brand name in a bold, white, sans-serif typeface. The background is a gradient of green and blue with large white circular shapes and four light bulbs (three unlit, one lit).


MOTION SENSOR LIGHTING

- 💡 Energy Efficient Devices
- 💡 Save upto 50% more

BULB

The Bulb Glows At Maximum Luminosity When Motion Is Detected And Automatically Switches-off After 60 Seconds Of No Movement.

MODEL NO	AUMBLB10XM
WATTAGE	10W
TYPE	HF SENSOR BULB
BASE TYPE:	B22/E27
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
SENSING ANGLE	120°
FEATURE	ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	ALUMINUM / POLYCARBONATE
LIFETIME	50,000 HOURS



WATTAGE

10W

DIMMING



MOTION ON/OFF



APPLICATION AREAS



CORRIDOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF



DOWNLIGHT

The light glows at maximum luminosity when motion is detected and automatically dims down or switches-off after 60 seconds of no movement.

MODEL NO

AUMDWN10XM

WATTAGE

10W

TYPE

CONCEALED ROUND

INPUT VOLTAGE

220-240V

SENSOR RANGE

UPTO 6 METERS

BEAM / SENSING ANGLE

120° / 360°

FEATURE

ON-OFF

COLOR TEMPERATURE

COOL WHITE

MATERIAL


PLOYCARBONATE

LIFETIME

50,000 HOURS

DIAMETER / CUT DIAMETER

115MM / 70MM



APPLICATION AREAS



CORRIDOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET

WATTAGE

10W

DIMMING



MOTION ON/OFF



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF




OVER CURRENT
PROTECTION

PANEL LIGHT ROUND

The light glows at maximum luminosity when motion is detected and automatically dims down or switches-off after 60 seconds of no movement.

MODEL NO	AUMPNR _{xyyy}
WATTAGE	12W, 15W, 20W
TYPE	ROUND
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
BEAM / SENSING ANGLE	120° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	PLOYCARBONATE
LIFETIME	50,000 HOURS
DIAMETER / CUT DIAMETER	140MM / 70MM



WATTAGE	DIMMING	MOTION ON/OFF
12W	AUMPNR12DM	AUMPNR12XM
15W	AUMPNR15DM	AUMPNR15XM
20W	AUMPNR20DM	AUMPNR20XM

APPLICATION AREAS



CORRIDOOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



OFFICE



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION




DIMMABLE

PANEL LIGHT SQUARE

The light glows at maximum luminosity when motion is detected and automatically dims down or switches-off after 60 seconds of no movement.



MODEL NO	AUMPNSxxyy
WATTAGE	12W, 15W, 20W
TYPE	SQUARE
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
BEAM / SENSING ANGLE	120° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	PLOYCARBONATE
LIFETIME	50,000 HOURS



WATTAGE	DIMMING	MOTION ON/OFF
12W	AUMPNS12DM	AUMPNS12XM
15W	AUMPNS15DM	AUMPNS15XM
20W	AUMPNS20DM	AUMPNS20XM

APPLICATION AREAS



CORRIDOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



OFFICE



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION




DIMMABLE

TUBE LIGHT T5

The light glows at maximum luminosity when motion is detected and automatically dims down to 30% capacity or switches-off after 45 seconds of no movement.

MODEL NO	AUMTLP _{XXXX}
WATTAGE	18W, 22W, 36W
TYPE	T5
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
BEAM / SENSING ANGLE	120° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	PLOYCARBONATE
LIFETIME	50,000 HOURS



WATTAGE	DIMMING	MOTION ON/OFF
18W	AUMTLP18DM	AUMTLP18XM
22W	AUMTLP22DM	AUMTLP22XM
36W	AUMTLP36DM	AUMTLP36XM

APPLICATION AREAS



CORRIDOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF




OVER CURRENT
PROTECTION




DIMMABLE

TUBE LIGHT T8

The light glows at maximum luminosity when motion is detected and automatically dims down to 30% capacity or switches-off after 45 seconds of no movement.



MODEL NO	AUMTLA _{XXXX}
WATTAGE	18W, 22W, 36W
TYPE	T8
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
BEAM / SENSING ANGLE	120° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	ALUMINUM
LIFETIME	50,000 HOURS



WATTAGE	DIMMING	MOTION ON/OFF
18W	AUMTLA18DM	AUMTLA18XM
22W	AUMTLA22DM	AUMTLA22XM
36W	AUMTLA36DM	AUMTLA36XM

APPLICATION AREAS



CORRIDOOR



RESIDENCE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION




DIMMABLE

RETRO TUBE T8

The light glows at maximum luminosity when motion is detected and automatically dims down to 30% capacity or switches-off after 45 seconds of no movement.

MODEL NO	AUMTLT _{xxyy}
WATTAGE	18W, 22W
TYPE	T8
INPUT VOLTAGE	220-240V
SENSOR RANGE	UPTO 6 METERS
BEAM / SENSING ANGLE	120° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	POLYCARBONATE
LIFETIME	50,000 HOURS
LENGTH / RADIUS	1190MM / 22MM



APPLICATION AREAS



CORRIDOR



PARKING



HALLWAY



WAREHOUSE



STAIRWAY



TOILET

WATTAGE

18W

22W

DIMMING

AUMTLT18DM

AUMTLT22DM

MOTION ON/OFF

AUMTLT18XM

AUMTLT22XM



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION




DIMMABLE

BULKHEAD LIGHT

The light glows at maximum luminosity when motion is detected and automatically dims down to 30% capacity or switches-off after 60 seconds of no movement.

MODEL NO	AUMBLKxxyy
WATTAGE	12W, 15W, 20W
TYPE	MOTION SENSOR IP65
INPUT VOLTAGE	90-260V
SENSOR RANGE	UPTO 7 METERS
BEAM / SENSING ANGLE	360° / 360°
FEATURE	DIMM / ON-OFF / PHOTSENSOR
COLOR TEMPERATURE	COOL WHITE
MATERIAL	POLYCARBONATE
LIFETIME	35,000 HOURS
LENGTH / WIDTH / HEIGHT	210MM / 95MM / 65MM
INGRESS PROTECTION	IP65
OPERATING TEMPERATURE	-20° TO 60°



APPLICATION AREAS



CORRIDOOR



PARKING



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



RESIDENCE

WATTAGE	DIMMING	MOTION ON/OFF	PHOTOSENSOR
12W	AUMBLK12DM	AUMBLK12XM	AUMBLK12XPH
15W	AUMBLK15DM	AUMBLK15XM	AUMBLK15XPH
20W	AUMBLK20DM	AUMBLK20XM	AUMBLK20XPH



HUMAN BODY
DETECTION



ENERGY
SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION



DIMMABLE




DAY/NIGHT


STREET LIGHT

The light glows at maximum luminosity when motion is detected and automatically dims down to 30% capacity or switches-off after 60 seconds of no movement.

MODEL NO	AUMSTL _{xyy}
WATTAGE	30W, 50W, 100W
TYPE	MOTION SENSOR IP65
INPUT VOLTAGE	90-260V
SENSOR RANGE	UPTO 10 METERS
BEAM / SENSING ANGLE	360° / 360°
FEATURE	DIMM / ON-OFF
COLOR TEMPERATURE	COOL WHITE
MATERIAL	ALUMINUM PRESSURE DIE CAST
LIFETIME	35,000 HOURS
LENGTH / WIDTH / HEIGHT	340MM / 125MM / 45MM
INGRESS PROTECTION	IP65
OPERATING TEMPERATURE	-20° TO 60°



APPLICATION AREAS



HIGHWAY



PARKING



CAMPUS



WAREHOUSE



PARK



DRIVEWAY



RESIDENCE

WATTAGE

36W

50W

100W

DIMMING

AUMSTL36DM

AUMSTL50DM

AUMSTL100DM

MOTION ON/OFF

AUMSTL36XM

AUMSTL50XM

AUMSTL100XM



HUMAN BODY
DETECTION



ENERGY
SAVING



1 YEAR
WARRANTY



ON/OFF



OVER CURRENT
PROTECTION



DIMMABLE




IP65

MICROWAVE SENSOR

This sensor gets retro-fitted with your existing luminaire and makes them Motion dependent. It turns on the device when motion is detected and swithes - off after a set adjustable delay time.



MODEL NO	AUMMWS06I
LOAD POWER	1200W (INCANDESCENT LAMP) OR 300W (ENERGY SAVING LAMP)
LOAD TYPE	INCANDESCENT LAMP, LED LIGHT, CFL
INPUT VOLTAGE	220-250V
SENSOR RANGE	UPTO 6 METERS
HF SYSTEM	5.8 GHZ CW RADAR, ISM BAND
SENSING ANGLE	360*
FEATURE	ON-OFF
MATERIAL	POLYCARBONATE
DELAY	10 SEC TO 12 MINS (ADJUSTABLE)
INGRESS PROTECTION	IP20
POWER CONSUMPTION	0.1W (STATIC) & 0.4W (WORKING)
MAX. HEIGHT FOR INSTALLATION	2.8 METERS



APPLICATION AREAS



CORRIDOOR



OFFICE



CONFERENCE ROOM



WAREHOUSE



HALLWAY



TOILET



STAIRWAY



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY




ON/OFF

PIR SENSOR

This sensor gets retro-fitted with your existing luminaire and makes them Motion dependent. It turns on the device when motion is detected and swithes - off after a set adjustable delay time.

MODEL NO	AUMPIR06I
LOAD POWER	1000W (INCANDESCENT LAMP) OR 280W (ENERGY SAVING LAMP)
LOAD TYPE	INCANDESCENT LAMP, LED LIGHT, CFL
TYPE	FALSE CEILING MOUNT
INPUT VOLTAGE	220-250V
SENSOR RANGE	UPTO 6 METERS
HF SYSTEM	5.8 GHZ CW RADAR, ISM BAND
SENSING ANGLE	360*
FEATURE	ON-OFF
MATERIAL	POLYCARBONATE
DELAY	10 SEC TO 12 MINS (ADJUSTABLE)
INGRESS PROTECTION	IP20
POWER CONSUMPTION	0.1W (STATIC) & 0.4W (WORKING)
MAX. HEIGHT FOR INSTALLATION	2.8 METERS



APPLICATION AREAS



CORRIDOOR



OFFICE



HALLWAY



WAREHOUSE



STAIRWAY



TOILET



HUMAN BODY
DETECTION



ENERGY SAVING



1 YEAR
WARRANTY



ON/OFF

VENTUM ES-28




1200 mm, BLDC CEILING FAN (BASE MODEL)

COLOUR VARIANTS

 BROWN  WHITE  IVORY

TECHNICAL SPECIFICATION


Sweep In MM	Input Power In Watts	Speed In RPM	Air Delivery In CMM	Service Value in CMM/W
1200	28	370	220	7.85



Above performance figure are subjected to tolerance and minimum value as stipulated in IS 374-2019

- 2 Years Warranty For Free Replacement Of Motor Against Manufacturing Defect.
- Super Energy Efficient Bldc Motor
- Inverter Stabilization Technology To Run Consistently At Same Speed With Voltage Variation For 130-280 Volt
- Smart Remote With Features Like Boost, Speed Control Mode
- Saving In Electricity Bill Up To Around 1500/- Per Year
- Runs 3 Times Longer On Inverter Battery As Compared To Ordinary Fan.
- Alum Body And Alum. Blade Construction With Ir Sensor Located In Bottom Cover And Covered By Suitable Cap
- Bee 5 Star Rated

LIGHT MANAGEMENT SYSTEM-CUSTOM SOLUTIONS



OPERATING VOLTAGE
BASE STATION NETWORK
WIRELESS NETWORK
CLOUD SERVICES
WORKING RANGE
BOX INGRESS
SENSOR

110-250V
GPRS, 3G
WIFI, BLE, LORA, RF
AWS, AZURE
500MTRS - 5KMS
IP65
PIR, MICROWAVE



HUMAN BODY
DETECTION




ENERGY SAVING




1 YEAR
WARRANTY



ON/OFF





LET US SWITCH-OFF YOUR LIGHTS AFTER USE!



AUMOS: A BRAND OF FUNSCHOLAR INNOVATIONS PVT LTD

📍 59B, CHOWRINGHEE ROAD, 6TH FLOOR, KOLKATA - 700020

✉️ INFO@FUNSCHOLAR.COM 🖱️ WWW.FUNSCHOLAR.COM

☎️ 033-40620267